



Features ActivePure® Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The ActivePure® Transit Guardian - External is designed to be mounted on the wall, ceiling or floor of a public transport vehicle (bus or train). Patented ActivePure is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2 – RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- MS2 Bacteriophage
- MRSA
- E. coli
- Salmonella enterica
- Legionella pneumophila
- Clostridium difficile
- Bacillus globigii
- Erwinia herbicola
- Listeria monocytogenes
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Aspergillus versicolor
- Aspergillus niger endospores
- Methicillin-resistant Staphylococcus epidermis
- Staphylococcus epidermidis

THE BENEFITS

The ActivePure Transit Guardian - External utilizes ActivePure Technology to help reduce viruses, bacteria, and other contaminants in the ambient air and on surfaces.

- Commercial vehicle air purification system
- Provides 24/7 surface decontamination and air purification
- Removes allergy and asthma triggering contaminants
- Compact, natural air treatment system for up to 350 sq. ft.

Live Fully With Confidence™



SPECIFICATIONS

Product Information 00775 Model: B101B

Technology Included ActivePure®

Electrical
Input Voltage: 12~14 VDC
Negative Grounded System
Current: 2.04 A
Complies to UL 507

Mechanical Airflow: 50 CFM

Sound Level 67 dB(A)

Weight & Dimensions
2.4 kg
12 cm x 33.02 cm x 19.05 cm
*w/ mounting hardware

Operating Temp. 1°C – 93°C

Recommended Maximum Coverage in a Contiguous Space*
Up to 31m² depending on occupant density and other factors.
Not for use in medical or health care environments.
*Depending on occupant density and other factors.

